

**FAG****NJ2340-EX-TB-MPAX-ILR**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E..-MPAX-ILR, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Technical information

**Your current product variant**

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	420 mm	Outside diameter
B	138 mm	Width
C_r	2.550.000 N	Basic dynamic load rating, radial
C_{0r}	2.900.000 N	Basic static load rating, radial
C_{ur}	315.000 N	Fatigue load limit, radial
n_G	2.330 1/min	Limiting speed
n_{gr}	940 1/min	Reference speed
$\approx m$	96,6 kg	Weight

Mounting dimensions

$d_{a \min}$	220 mm	Minimum diameter shaft shoulder
$d_{a \max}$	250,7 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	400 mm	Maximum diameter of housing shoulder









Dimensions

r_{min}	5 mm	Minimum chamfer dimension
$r_{1 min}$	5 mm	Minimum chamfer dimension
s	11,3 mm	Axial displacement
E	377 mm	Raceway diameter outer ring
F	253 mm	Raceway diameter inner ring
$D_{1 min}$	352,2 mm	Minimum rib diameter outer ring
d_1	200 mm	Maximum rib diameter inner ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing