



HXPM-50T-2/3-ARM-SHORT [↗](#)

Mobile hydraulic heavy duty hook puller

BETEX HXPM, 2/3-arm self-centering, max. pull-off force 490 kN, short version, mobile

Technical information

Your current product variant

Series	HXPM	With cart
--------	------	-----------

Technical data

U	230 V	Voltage
	AC power	Current type
f	50 – 60 Hz	Power frequency
s _{cm max}	330 mm	Max. working stroke main cylinder
P _{max}	700 bar	Max. operating pressure
w _{min}	200 mm	Grip width, min.
w _{max}	950 mm	Grip width, max.
t _{max}	500 mm	Grip depth, max.
F _p	490 kN	Pulling force
	820 – 1370	Working height range [bottom – center axis cylinder] (mm)
	2245 x 800 x 1155	Dimensions [LxWxH] (mm)
≈m	385 kg	Weight



Additional information

electrically operated hydraulic unit for main cylinder and height adjustment, safety valve prevents overload, opening and closing of the gripper arms by means of hand pump	Functional principle
two- or three-arm puller (convertible)	Usability
2 swivel castors with brake function, 2 fixed castors	Castors
Remote control, 4 adapter pieces (total length 620 mm), security blanket	Included in delivery