



## HXPM-100T-2-ARM [↗](#)

Mobile hydraulic heavy duty hook puller

BETEX HXPM, 2-arm self-centering, max. pull-off force 980 kN, mobile

### Technical information

#### Your current product variant

|        |      |           |
|--------|------|-----------|
| Series | HXPM | With cart |
|--------|------|-----------|

#### Technical data

|          |                    |   |
|----------|--------------------|---|
| U        | 400 V              | Voltage   |
|          | Three-phase AC     | Current type  |
| f        | 50 – 60 Hz         | Power frequency   |
| s cm max | 270 mm             | Max. working stroke main cylinder                         |
| P max    | 700 bar            | Max. operating pressure                                   |
| w min    | 300 mm             | Grip width, min.  |
| w max    | 1.500 mm           | Grip width, max.  |
| t max    | 1.220 mm           | Grip depth, max.  |
| F p      | 980 kN             | Pulling force   |
|          | 320 – 790          | Working height range [bottom – center axis cylinder] (mm) |
|          | 2450 x 1350 x 1200 | Dimensions [LxWxH] (mm)                                   |
| m        | 870 kg             | Weight  |



### Additional information

---

electrically operated hydraulic unit for main cylinder, height adjustment as well as opening and closing of the gripper arms, safety valve prevents overloading

Functional principle

2 swivel castors with brake function, 2 fixed castors

Castors

Remote control, 7 adapter pieces (total length 1125 mm), security blanket

Included in delivery