

**FAG****61803-2RSR-C3>N**

Deep groove ball bearing

Deep groove ball bearing 618...-2RSR, single row, seals, steel sheet metal cage

## Technical information

**Your current product variant**

|                                  |                    |   |
|----------------------------------|--------------------|---|
| Version code                     | >N                 | Not marked on bearing                   |
| Sealing                          | 2RSR               | Contact seal on both sides              |
| Cage                             | JN                 | Steel sheet metal                       |
| Tolerance class                  | PN                 | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN                 | Rings dimensional stabilized up to 120° |
| Lubricant                        | Lubricating grease |   |
| Radial internal clearance        | C3 (Group 3)       | Internal clearance larger than CN       |
| Bore type                        | Z                  | Cylindrical                             |

**Main Dimensions & Performance Data**

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 17 mm        | Bore diameter                     |
| D               | 26 mm        | Outside diameter                  |
| B               | 5 mm         | Width                             |
| C <sub>r</sub>  | 2.270 N      | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.370 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 84 N         | Fatigue load limit, radial        |
| n <sub>G</sub>  | 13.600 1/min | Limiting speed                    |
| ≈m              | 7,2 g        | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 19 mm  | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 24 mm  | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,3 mm | Maximum fillet radius                |

### Dimensions

|            |         |                              |
|------------|---------|------------------------------|
| $r_{\min}$ | 0,3 mm  | Minimum chamfer dimension    |
| $D_1$      | 23,3 mm | Shoulder diameter outer ring |
| $D_2$      | 24,1 mm | Caliber diameter outer ring  |
| $d_1$      | 19,7 mm | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 16,1 | Calculation factor |
|-------|------|--------------------|

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides