

**FAG****61805-2RSR-C3>N**

Deep groove ball bearing

Deep groove ball bearing 618...2RSR, single row, seals, steel sheet metal cage

## Technical information

**Your current product variant**

Version code	>N	Not marked on bearing
Type of Seal	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
D	37 mm	Outside diameter
B	7 mm	Width
C <sub>r</sub>	4.550 N	Basic dynamic load rating, radial
C <sub>0r</sub>	2.950 N	Basic static load rating, radial
C <sub>ur</sub>	182 N	Fatigue load limit, radial
n <sub>G</sub>	9.600 1/min	Limiting speed
≈m	0,022 kg	Weight



### Mounting dimensions

$d_{a \min}$	27 mm	Minimum diameter shaft shoulder
$D_{a \max}$	35 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	33,4 mm	Shoulder diameter outer ring
$D_2$	34,4 mm	Caliber diameter outer ring
$d_1$	28,6 mm	Shoulder diameter inner ring
$d_2$	27,9 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	16,1	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides