

**FAG****61909-2Z>N**

Deep groove ball bearing

Deep groove ball bearing 619..-2Z, single row, shields, steel sheet metal cage

Technical information



Your current product variant

| | | |
|----------------------------------|--------------------|---|
| Version code | >N | Not marked on bearing |
| Sealing | 2Z | Non-contact shield on both sides |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | Lubricating grease | |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|----------|--------------|-----------------------------------|
| d | 45 mm | Bore diameter |
| D | 68 mm | Outside diameter |
| B | 12 mm | Width |
| C_r | 14.300 N | Basic dynamic load rating, radial |
| C_{0r} | 10.100 N | Basic static load rating, radial |
| C_{ur} | 630 N | Fatigue load limit, radial |
| n_G | 12.300 1/min | Limiting speed |
| n_{gr} | 9.000 1/min | Reference speed |
| m | 0,13 kg | Weight |



Mounting dimensions

| | | |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 48,2 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 64,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|---------|------------------------------|
| r_{\min} | 0,6 mm | Minimum chamfer dimension |
| D_1 | 60,5 mm | Shoulder diameter outer ring |
| D_2 | 62,5 mm | Caliber diameter outer ring |
| d_1 | 51,5 mm | Shoulder diameter inner ring |
| d_2 | 50,5 mm | Caliber diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 15,8 | Calculation factor |
|-------|------|--------------------|

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication |
|  | Sealed on both sides |