

**FAG****61807>N**

## Deep groove ball bearing

Deep groove ball bearing 618, single row,  
steel sheet metal cage

## Technical information



## Your current product variant

|                                  |              |   |
|----------------------------------|--------------|---|
| Version code                     | >N           | Not marked on bearing                   |
| Sealing                          | Without      | Not sealed                              |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | CN (Group N) | Normal internal clearance               |
| Bore type                        | Z            | Cylindrical                             |

## Main Dimensions &amp; Performance Data

|          |              |                                   |
|----------|--------------|-----------------------------------|
| d        | 35 mm        | Bore diameter                     |
| D        | 47 mm        | Outside diameter                  |
| B        | 7 mm         | Width                             |
| $C_r$    | 4.550 N      | Basic dynamic load rating, radial |
| $C_{0r}$ | 3.600 N      | Basic static load rating, radial  |
| $C_{ur}$ | 211 N        | Fatigue load limit, radial        |
| $n_G$    | 21.500 1/min | Limiting speed                    |
| $n_{gr}$ | 9.600 1/min  | Reference speed                   |
| $m$      | 0,029 kg     | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 37 mm  | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 45 mm  | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,3 mm | Maximum fillet radius                |

### Dimensions

|            |         |                              |
|------------|---------|------------------------------|
| $r_{\min}$ | 0,3 mm  | Minimum chamfer dimension    |
| $D_1$      | 43,3 mm | Shoulder diameter outer ring |
| $D_2$      | 44,3 mm | Caliber diameter outer ring  |
| $d_1$      | 38,7 mm | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 16,2 | Calculation factor |
|-------|------|--------------------|

### Characteristics

|   |                              |
|---|------------------------------|
|  | Radial load                  |
|  | Axial load in one direction  |
|  | Axial load in two directions |
|  | Grease Lubrication           |
|  | Oil Lubrication              |
|  | Not sealed                   |