

**FAG****6303-H-2Z>N**

Deep groove ball bearing

Deep groove ball bearing 63...-H-2Z, single row, H-Series, shields, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>N	Not marked on bearing
Changed internal design	H	Design variant H (H-Series)
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	17 mm	Bore diameter
D	47 mm	Outside diameter
B	14 mm	Width
C <sub>r</sub>	13.580 N	Basic dynamic load rating, radial
C <sub>0r</sub>	6.580 N	Basic static load rating, radial
C <sub>ur</sub>	390 N	Fatigue load limit, radial
n <sub>G</sub>	18.700 1/min	Limiting speed
n <sub>gr</sub>	15.500 1/min	Reference speed
≈m	0,113 kg	Weight



### Mounting dimensions

$d_{a \min}$	22,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	41,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	38,2 mm	Shoulder diameter outer ring
$D_2$	40,1 mm	Caliber diameter outer ring
$d_1$	26,8 mm	Shoulder diameter inner ring
$d_2$	25,2 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	12,4	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides