



## RCJTY30-VA-FD [↗](#)

Flanged housing unit

### Technical information

#### Your current product variant

Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

#### Main Dimensions & Performance Data

d	30 mm	Bore diameter
L	76 mm	Flange width
H	148 mm	Height flange
U	40,2 mm	Total height unit
C <sub>r</sub>	16.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	9.110 N	Basic static load rating, radial
C <sub>ur</sub>	760 N	Fatigue load limit, radial
≈m	1,06 kg	Weight

#### Mounting dimensions

J	117 mm	Distance fixing bore
N	16 mm	Fixing bore
W	3 mm	Width across flats

#### Dimensions

A	32,5 mm	Height housing
A <sub>1</sub>	10 mm	Thickness of flange
A <sub>2</sub>	18 mm	Distance raceway



### Additional information

GEH.CJT06-VA-NAT	Housing
YE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.