



## RCJY35-VA-FD

Flanged housing unit

### Technical information

#### Your current product variant

Special material	TV	Plastic housing
Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

#### Main Dimensions & Performance Data

d	35 mm	Bore diameter
L	117 mm	Flange width
U	44,4 mm	Total height unit
C <sub>r</sub>	21.900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	12.500 N	Basic static load rating, radial
C <sub>ur</sub>	1.000 N	Fatigue load limit, radial
≈m	1,26 kg	Weight

#### Mounting dimensions

J	92 mm	Distance fixing bore
N	14 mm	Fixing bore
W	4 mm	Width of flats

#### Dimensions

A	34 mm	Height housing
A <sub>1</sub>	11 mm	Thickness of flange
A <sub>2</sub>	19 mm	Distance raceway



### Additional information

GEH.CJ07-VA-NAT	Housing
YE35-DC-B-VA-FD	Bearing designation
KASK07-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.