

**RCJTY35-VA-FD** [↗](#)

Flanged housing unit

## Technical information

**Your current product variant**

Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
L	86 mm	Flange width
H	161 mm	Height flange
U	44,4 mm	Total height unit
C <sub>r</sub>	21.900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	12.500 N	Basic static load rating, radial
C <sub>ur</sub>	1.000 N	Fatigue load limit, radial
≈m	1,33 kg	Weight

**Mounting dimensions**

J	130 mm	Distance fixing bore
N	16 mm	Fixing bore
W	4 mm	Width across flats

**Dimensions**

A	34 mm	Height housing
A <sub>1</sub>	11 mm	Thickness of flange
A <sub>2</sub>	19 mm	Distance raceway



### Additional information

GEH.CJT07-VA-NAT	Housing
YE35-DC-B-VA-FD	Bearing designation
KASK07-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.