

**RASEY40-VA-FD**

Plummer block housing unit

## Technical information

**Your current product variant**

Material	VA	Stainless Steel
Special material	VA	Corrosion-resistant VA design

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
L	184 mm	Length total
H <sub>2</sub>	96,2 mm	Height
U	50,2 mm	Total width unit
C <sub>r</sub>	24.900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	14.500 N	Basic static load rating, radial
C <sub>ur</sub>	1.130 N	Fatigue load limit, radial
≈m	1,78 kg	Weight

**Mounting dimensions**

J	137 mm	Distance fixing bore
N	17 mm	Width (slot)
N <sub>1</sub>	21 mm	Length (slot)



### Dimensions

H	49,2 mm	Distance shaft axis
A	40 mm	Width (base)
H <sub>1</sub>	14 mm	Height (base)
S <sub>1</sub>	31,2 mm	Distance of raceway to locking collar

### Additional information

GEH.ASE08-VA-NAT	Housing
YE40-DC-B-VA-FD	Bearing designation
KASK08-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.