

**FAG****6209-C-C3>V**

Deep groove ball bearing

Deep groove ball bearing 62...-C, single row,
Generation C, steel sheet metal cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|--------------|---|
| Version code | >V | Not marked on bearing |
| Changed internal design | C | GenerationC |
| Type of Seal | Without | Not sealed |
| Cage | JN | Steel sheet metal |
| Tolerance class | P6 | Class6 (P6), better then PN |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | Without | Bearing not greased |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|-----------------------------------|
| d | 45 mm | Bore diameter |
| D | 85 mm | Outside diameter |
| B | 19 mm | Width |
| C _r | 35.500 N | Basic dynamic load rating, radial |
| C _{0r} | 20.300 N | Basic static load rating, radial |
| C _{ur} | 1.400 N | Fatigue load limit, radial |
| n _G | 12.700 1/min | Limiting speed |
| n _{gr} | 9.900 1/min | Reference speed |
| ≈m | 0,39 kg | Weight |



Mounting dimensions

| | | |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 52 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 78 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| D_1 | 72,35 mm | Shoulder diameter outer ring |
| D_2 | 75,34 mm | Caliber diameter outer ring |
| d_1 | 56,63 mm | Shoulder diameter inner ring |
| d_2 | 54,04 mm | Caliber diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 14,3 | Calculation factor |
|-------|------|--------------------|

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |