

**RCJY30-VA-FD**

Flanged housing unit

## Technical information

**Your current product variant**

Special material	TV	Plastic housing
Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
L	108 mm	Flange width
U	40,2 mm	Total height unit
C <sub>r</sub>	16.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	9.110 N	Basic static load rating, radial
C <sub>ur</sub>	760 N	Fatigue load limit, radial
≈m	1 kg	Weight

**Mounting dimensions**

J	83 mm	Distance fixing bore
N	12 mm	Fixing bore
W	3 mm	Width of flats

**Dimensions**

A	32,5 mm	Height housing
A <sub>1</sub>	10 mm	Thickness of flange
A <sub>2</sub>	18 mm	Distance raceway



View product details on medias

07.05.2026, 21:13:26 UTC

SCHAEFFLER

### Additional information

GEH.CJ06-VA-NAT	Housing
YE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.