

**RASEOC30-VA-FD** [↗](#)

Plummer block housing unit

## Technical information

**Your current product variant**

Material	VA	Stainless Steel
----------	----	-----------------

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
L	165 mm	Length total
H <sub>2</sub>	80,9 mm	Height
U	41,8 mm	Total width unit
C <sub>r</sub>	16.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	9.110 N	Basic static load rating, radial
C <sub>ur</sub>	760 N	Fatigue load limit, radial
≈m	1,3 kg	Weight

**Mounting dimensions**

J	121 mm	Distance fixing bore
N	17 mm	Width (slot)
N <sub>1</sub>	21 mm	Length (slot)

**Dimensions**

H	42,9 mm	Distance shaft axis
A	36 mm	Width (base)
H <sub>1</sub>	13 mm	Height (base)
S <sub>1</sub>	23,8 mm	Distance of raceway to locking collar



### Additional information

---

GEH.ASE06-VA-NAT	Housing
OCE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

### Temperature range

---

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.