



## RASEOC25-VA-FD [↗](#)

Plummer block housing unit

### Technical information

#### Your current product variant

Material	VA	Stainless Steel
----------	----	-----------------

#### Main Dimensions & Performance Data

d	25 mm	Bore diameter
L	140 mm	Length total
H <sub>2</sub>	68 mm	Height
U	37,2 mm	Total width unit
C <sub>r</sub>	12.200 N	Basic dynamic load rating, radial
C <sub>0r</sub>	6.500 N	Basic static load rating, radial
C <sub>ur</sub>	550 N	Fatigue load limit, radial
≈m	0,78 kg	Weight

#### Mounting dimensions

J	105 mm	Distance fixing bore
N	13 mm	Width (slot)
N <sub>1</sub>	19 mm	Length (slot)

#### Dimensions

H	36,5 mm	Distance shaft axis
A	30 mm	Width (base)
H <sub>1</sub>	12 mm	Height (base)
S <sub>1</sub>	22,2 mm	Distance of raceway to locking collar



### Additional information

---

GEH.ASE05-VA-NAT	Housing
OCE25-DC-B-VA-FD	Bearing designation
KASK05-VA-G-NAT	Protecting cap

### Temperature range

---

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.