

**RCJY20-VA-FD**

Flanged housing unit

## Technical information

**Your current product variant**

Special material	TV	Plastic housing
Material	VA	Stainless Steel
Corrosion resistant bearing	VA	Corrosion-resistant VA design

**Main Dimensions & Performance Data**

d	20 mm	Bore diameter
L	86 mm	Flange width
U	34,1 mm	Total height unit
C <sub>r</sub>	11.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	5.400 N	Basic static load rating, radial
C <sub>ur</sub>	500 N	Fatigue load limit, radial
≈m	0,57 kg	Weight

**Mounting dimensions**

J	64 mm	Distance fixing bore
N	12 mm	Fixing bore
W	2,5 mm	Width of flats

**Dimensions**

A	28 mm	Height housing
A <sub>1</sub>	10 mm	Thickness of flange
A <sub>2</sub>	15 mm	Distance raceway



### Additional information

GEH.CJ04-VA-NAT	Housing
YE20-DC-B-VA-FD	Bearing designation
KASK04-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.