

**RASEHOC20-VA-FD** [↗](#)

Plummer block housing unit

## Technical information

**Your current product variant**

Material	VA	Stainless Steel
----------	----	-----------------

**Main Dimensions & Performance Data**

d	20 mm	Bore diameter
L	127 mm	Length total
H <sub>2</sub>	74,5 mm	Height
U	34,8 mm	Total width unit
C <sub>r</sub>	11.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	5.400 N	Basic static load rating, radial
C <sub>ur</sub>	500 N	Fatigue load limit, radial
≈m	0,7 kg	Weight

**Mounting dimensions**

J	95 mm	Distance fixing bore
N	13 mm	Width (slot)
N <sub>1</sub>	18 mm	Length (slot)



### Dimensions

H	46 mm	Distance shaft axis
A	30 mm	Width (base)
H <sub>1</sub>	23,7 mm	Height (base)
Y	12,7 mm	Distance housing base
S <sub>1</sub>	20,6 mm	Distance of raceway to locking collar

### Additional information

GEH.ASE04H-VA-NAT	Housing
OCE20-DC-B-VA-FD	Bearing designation
KASK04-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.