



## RASEHY25-VA-FD [↗](#)

Plummer block housing unit

### Technical information

#### Your current product variant

Material	VA	Stainless Steel
Special material	VA	Corrosion-resistant VA design

#### Main Dimensions & Performance Data

d	25 mm	Bore diameter
L	140 mm	Length total
H <sub>2</sub>	80,7 mm	Height
U	34,8 mm	Total width unit
C <sub>r</sub>	12.200 N	Basic dynamic load rating, radial
C <sub>0r</sub>	6.500 N	Basic static load rating, radial
C <sub>ur</sub>	550 N	Fatigue load limit, radial
≈m	0,77 kg	Weight

#### Mounting dimensions

J	105 mm	Distance fixing bore
N	13 mm	Width (slot)
N <sub>1</sub>	19 mm	Length (slot)



### Dimensions

H	49,2 mm	Distance shaft axis
A	30 mm	Width (base)
H <sub>1</sub>	24,7 mm	Height (base)
Y	12,7 mm	Distance housing base
S <sub>1</sub>	19,8 mm	Distance of raceway to locking collar

### Additional information

GEH.ASEH05-VA-NAT	Housing
YE25-DC-B-VA-FD	Bearing designation
KASK05-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.