



RASEHY35-VA-FD [↗](#)

Plummer block housing unit

Technical information

Your current product variant

Material	VA	Stainless Steel
Special material	VA	Corrosion-resistant VA design

Main Dimensions & Performance Data

d	35 mm	Bore diameter
L	167 mm	Length total
H ₂	103,3 mm	Height
U	44,4 mm	Total width unit
C _r	21.900 N	Basic dynamic load rating, radial
C _{0r}	12.500 N	Basic static load rating, radial
C _{ur}	1.000 N	Fatigue load limit, radial
≈m	1,59 kg	Weight

Mounting dimensions

J	127 mm	Distance fixing bore
N	17 mm	Width (slot)
N ₁	21 mm	Length (slot)



Dimensions

H	60,3 mm	Distance shaft axis
A	38 mm	Width (base)
H ₁	26,7 mm	Height (base)
Y	12,7 mm	Distance housing base
S ₁	25,4 mm	Distance of raceway to locking collar

Additional information

GEH.ASEH07-VA-NAT	Housing
YE35-DC-B-VA-FD	Bearing designation
KASK07-VA-G-NAT	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.