



## RSHEHY30-VA-FD

Plummer block housing unit

### Technical information

#### Your current product variant

Material	VA	Stainless Steel
----------	----	-----------------

#### Main Dimensions & Performance Data

d	30 mm	Bore diameter
L	96 mm	Length total
H <sub>2</sub>	93,6 mm	Height
U	40,2 mm	Total width unit
C <sub>r</sub>	16.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	9.110 N	Basic static load rating, radial
C <sub>ur</sub>	760 N	Fatigue load limit, radial
≈m	1,08 kg	Weight

#### Mounting dimensions

J	76,2 mm	Distance fixing bore
K	7/16-14UNC	Thread fixing bore
H <sub>3</sub>	18 mm	Thread length

#### Dimensions

H	55,6 mm	Distance shaft axis
A	36 mm	Width (base)
Y	12,7 mm	Distance housing base
S <sub>1</sub>	22,2 mm	Distance of raceway to locking collar



### Additional information

---

GEH.SHEH06-VA-NAT	Housing
YE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

### Temperature range

---

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.