

**RFBY20-VA-FD**

Flanged housing unit

## Technical information

**Your current product variant**

Material	VA	Stainless Steel
----------	----	-----------------

**Main Dimensions & Performance Data**

d	20 mm	Bore diameter
L	58 mm	Flange width
U	32,6 mm	Total height unit
C <sub>r</sub>	11.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	5.400 N	Basic static load rating, radial
C <sub>ur</sub>	500 N	Fatigue load limit, radial
H	105 mm	Height flange
≈m	0,43 kg	Weight

**Mounting dimensions**

J	38,1 mm	Distance fixing bore
N	12 mm	Fixing bore
n	3	Number of screwing holes
H <sub>1</sub>	42,9 mm	Distance fixing bore to bearing center
J <sub>1</sub>	22,2 mm	Distance fixing bore



### Dimensions

A	26,5 mm	Height housing
A <sub>1</sub>	8 mm	Thickness of flange
A <sub>2</sub>	13,5 mm	Distance raceway

### Additional information

GEH.FB04-VA-NAT	Housing
YE20-DC-B-VA-FD	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.