

**FAG****6308-C-2Z-L207-C3>V**

Deep groove ball bearing

Deep groove ball bearing 63...-C-2Z, single row, Generation C, shields, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L207	Low noise high-temperature grease, interchangeable with grease L069
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C <sub>r</sub>	50.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	25.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.730 N	Fatigue load limit, radial
n <sub>G</sub>	10.100 1/min	Limiting speed
n <sub>gr</sub>	9.900 1/min	Reference speed
≈m	0,619 kg	Weight



### Mounting dimensions

$d_{a \min}$	49 mm	Minimum diameter shaft shoulder
$D_{a \max}$	81 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	75,54 mm	Shoulder diameter outer ring
$D_2$	78,61 mm	Caliber diameter outer ring
$d_1$	55,08 mm	Shoulder diameter inner ring
$d_2$	52,28 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	13	Calculation factor
-------	----	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides