



**AP-3000S-HN-SET**

Hydraulic pump, air-driven

BETEX Air-hydraulic foot pump, 700 bar,  
in set with pressure gauge, T-piece, hose,  
couplings and steel box

## Technical information

**Your current product variant**

Series	AP	Air-hydraulic pump
Version	HN	For use with hydraulic nuts

**Technical data**

P <sub>max</sub>	700 bar	Maximum operating pressure
$\dot{V}$	195 cm <sup>3</sup> @ 700 bar	Oil flow/minute
V <sub>max</sub>	3 l	Volume of oil container
V <sub>eff</sub>	2,5 l	Useable oil quantity
P <sub>AIR</sub>	7 – 10 bar	Required pressure in the air supply
	3/8" NPT	Hose connection pump body
	Quick coupling G <sup>1</sup> / <sub>4</sub>	Coupling
	9,1 kg	Weight pump
	376 x 243 x 253	Dimensions steel case (mm)
=m	14,3 kg	Weight



### Dimensions

---

A	247 mm
B	190 mm
C	114 mm
D	309 mm
E	160 mm
F	90 mm
J	289 mm

### Additional information

---

preferably in combination with hydraulic nuts HYDNUT

Use

### Related products

---

HYDNUT..E  
HYDNUT..E-INCH  
HYDNUT..HEAVY