

**FAG****S698-2Z>N**

## Deep groove ball bearing

Deep groove ball bearing S69..-2Z, corrosion-resistant materials, single row, shields, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	8 mm	Bore diameter
D	19 mm	Outside diameter
B	6 mm	Width
$C_r$	2.390 N	Basic dynamic load rating, radial
$C_{0r}$	930 N	Basic static load rating, radial
$C_{ur}$	57 N	Fatigue load limit, radial
$n_G$	45.000 1/min	Limiting speed
$n_{gr}$	27.500 1/min	Reference speed
$\approx m$	7,57 g	Weight



### Mounting dimensions

$d_{a \min}$	10 mm	Minimum diameter shaft shoulder
$D_{a \max}$	17 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	16 mm	Shoulder diameter outer ring
$D_2$	16,4 mm	Caliber diameter outer ring
$d_1$	11 mm	Shoulder diameter inner ring
$d_2$	10,5 mm	Caliber diameter inner ring








### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	13,2	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Protected against rust