

**RTUEOC35-VA-FD** [↗](#)

Take-up housing unit

Technical information

Your current product variant

Material	VA	Stainless Steel
----------	----	-----------------

Main Dimensions & Performance Data

d	35 mm	Bore diameter
H	102 mm	Height
L	118 mm	Length total
B ₁	44,5 mm	Locking collar total width
C _{0r}	12.500 N	Basic static load rating, radial
C _{ur}	1.000 N	Fatigue load limit, radial
C _r	21.900 N	Basic dynamic load rating, radial
≈m	1,7 kg	Weight

Mounting dimensions

A ₁	12 mm	Width guidance groove
H ₁	89 mm	Distance guidance grooves
N	22 mm	Fixing bore



Dimensions

L ₁	75 mm	Distance shaft axis
L ₂	11 mm	Length fixed link
L ₃	56 mm	Length guidance groove
A	37 mm	Width housing fixing side
N ₁	18 mm	Width recess
N ₂	37 mm	Height recess
T	56 mm	Height housing fixing side
A ₂	31 mm	Width housing

Additional information

GEH.TUE07-VA-NAT	Housing
OCE35-DC-B-VA-FD	Bearing designation
KASK07-VA-G-NAT	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.