

**RTUEOC30-VA-FD** [↗](#)

Take-up housing unit

## Technical information

**Your current product variant**

Material	VA	Stainless Steel
----------	----	-----------------

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
H	102 mm	Height
L	105 mm	Length total
B <sub>1</sub>	40,4 mm	Locking collar total width
C <sub>0r</sub>	9.110 N	Basic static load rating, radial
C <sub>ur</sub>	760 N	Fatigue load limit, radial
C <sub>r</sub>	16.700 N	Basic dynamic load rating, radial
≈m	1,25 kg	Weight

**Mounting dimensions**

A <sub>1</sub>	12 mm	Width guidance groove
H <sub>1</sub>	89 mm	Distance guidance grooves
N	22 mm	Fixing bore



### Dimensions

L <sub>1</sub>	67 mm	Distance shaft axis
L <sub>2</sub>	9 mm	Length fixed link
L <sub>3</sub>	50 mm	Length guidance groove
A	37 mm	Width housing fixing side
N <sub>1</sub>	18 mm	Width recess
N <sub>2</sub>	37 mm	Height recess
T	52 mm	Height housing fixing side
A <sub>2</sub>	27 mm	Width housing

### Additional information

GEH.TUE06-VA-NAT	Housing
OCE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.