



## RSHEOC20-VA-FD [↗](#)

Plummer block housing unit

### Technical information

#### Your current product variant

Material	VA	Stainless Steel
----------	----	-----------------

#### Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	76 mm	Length total
H <sub>2</sub>	58,7 mm	Height
U	34,8 mm	Total width unit
C <sub>r</sub>	11.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	5.400 N	Basic static load rating, radial
C <sub>ur</sub>	500 N	Fatigue load limit, radial
≈m	0,48 kg	Weight

#### Mounting dimensions

J	50,8 mm	Distance fixing bore
K	3/8-16UNC	Thread fixing bore
H <sub>3</sub>	13 mm	Thread length

#### Dimensions

H	33,3 mm	Distance shaft axis
A	30 mm	Width (base)
S <sub>1</sub>	20,6 mm	Distance of raceway to locking collar



### Additional information

---

GEH.SHE04-VA-NAT	Housing
OCE20-DC-B-VA-FD	Bearing designation
KASK04-VA-G-NAT	Protecting cap

### Temperature range

---

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.