



RTUEY30-VA-FD [↗](#)

Take-up housing unit

Technical information

Your current product variant

Material	VA	Stainless Steel
----------	----	-----------------

Main Dimensions & Performance Data

d	30 mm	Bore diameter
H	102 mm	Height
L	105 mm	Length total
C _{0r}	9.110 N	Basic static load rating, radial
C _{ur}	760 N	Fatigue load limit, radial
C _r	16.700 N	Basic dynamic load rating, radial
≈m	1,19 kg	Weight

Mounting dimensions

A ₁	12 mm	Width guidance groove
H ₁	89 mm	Distance guidance grooves
N	22 mm	Fixing bore



Dimensions

L ₁	67 mm	Distance shaft axis
L ₂	9 mm	Length fixed link
L ₃	50 mm	Length guidance groove
A	37 mm	Width housing fixing side
N ₁	18 mm	Width recess
N ₂	37 mm	Height recess
B	38,1 mm	Width inner ring
T	52 mm	Height housing fixing side
A ₂	27 mm	Width housing

Additional information

GEH.TUE06-VA-NAT	Housing
YE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.