

**GF40-DO** [↗](#)

## Rod end

Hydraulic rod end, with rectangular welding face, requiring maintenance, sliding contact surface: steel/steel, open design

## Technical information

**Your current product variant**

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)
Slotted	No
Sealing	Without
Mounting	Weldable, rectangular

**Main Dimensions & Performance Data**

$C_r$	129.000 N	Basic dynamic load rating, radial
$C_{0r}$	306.000 N	Basic static load rating, radial
$d$	40 mm	Bore diameter bearing
$d_2$	100 mm	Outer eye diameter
$l_6$	119 mm	Total length welding head
$D$	62 mm	Outside diameter bearing
$B$	28 mm	Width inner ring
$\approx m$	2,39 kg	Weight



## Dimensions

$d_K$	53 mm	Ball diameter
$\alpha$	7 °	Tilt angle
$C_1$	35 mm	Width of the rod end
$C_{1\max}$	35,9 mm	Width of the rod end, max.
$h_2$	69 mm	Shank Length Welding Head
$d_{UT}$	-0,012 mm	Bore diameter bearing, lower tolerance
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$G_r$	0,043-0,12	Radial Clearance
$G_{r\max}$	0,12 mm	Radial clearance, maximum
$G_{r\min}$	0,043 mm	Radial clearance, minimum

## Mounting dimensions

$r_{1\min}$	0,6 mm	Edge Spacing
$d_1$	45 mm	Outer flange diameter inner ring

## Temperature range

$T_{\min}$	-60 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment