

**GF30-DO**

## Rod end

Hydraulic rod end, with rectangular welding face, requiring maintenance, sliding contact surface: steel/steel, open design

## Technical information



## Your current product variant

Clampable	Not clampable
Maintenance	Maintenance required
Mounting	Weldable, rectangular
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)
Slotted	No
Type of Seal	Without

## Main Dimensions &amp; Performance Data

$C_r$	81.000 N	Basic dynamic load rating, radial
$C_{0r}$	116.000 N	Basic static load rating, radial
$d$	30 mm	Bore diameter bearing
$d_2$	65 mm	Outer eye diameter
$l_6$	83,5 mm	Total length welding head
$D$	47 mm	Outside diameter bearing
$B$	22 mm	Width inner ring
$\approx m$	0,83 kg	Weight



## Dimensions

$d_K$	40,7 mm	Ball diameter
$\alpha$	6 °	Tilt angle
$C_1$	28 mm	Width of the rod end
$C_{1\max}$	28,5 mm	Width of the rod end, max.
$h_2$	51 mm	Shank Length Welding Head
$d_{UT}$	-0,01 mm	Bore diameter bearing, lower tolerance
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$G_r$	0,037-0,1	Radial Clearance
$G_{r\max}$	0,1 mm	Radial clearance, maximum
$G_{r\min}$	0,037 mm	Radial clearance, minimum

## Mounting dimensions

$r_{1\min}$	0,6 mm	Edge Spacing
$d_1$	34,2 mm	Outer flange diameter inner ring

## Temperature range

$T_{\min}$	-60 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment