


**GIHNRK40-LO**

Rod end



Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN 24338 ISO 6982, open design

Technical information

**Your current product variant**

Clampable	Clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	Slotted, both sides	
Thread Pitch	Right-hand thread	
Sealing	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	Internal thread clampable	

Main Dimensions & Performance Data

C_r	129.000 N	Basic dynamic load rating, radial
C_{0r}	219.000 N	Basic static load rating, radial
d	40 mm	Bore diameter bearing
d_2	89 mm	Outer eye diameter
l_4	146 mm	Total length internal thread head
D	62 mm	Outside diameter bearing
B	40 mm	Width inner ring
$\approx m$	2,1 kg	Weight



Dimensions

α	4 °	Tilt angle
C 1	33 mm	Width of the rod end
C 2	26 mm	Width
d K	53 mm	Ball diameter
d 3	M33x2	Thread size
d 4	47 mm	Shank diameter
d 5	80 mm	Shank diameter, large
d 7	M10x25	Diameter screw clamp
h 1	97 mm	Shank Length Internal thread head
l 3	46 mm	Thread length Internal thread
l 7	41 mm	Distance drilling with/shaft start
d UT	0 mm	Bore diameter bearing, lower tolerance
d T	H7	Bore diameter bearing, tolerance
d OT	0,025 mm	Bore diameter bearing, upper tolerance
B UT	-0,25 mm	Width inner ring, lower tolerance
B OT	0 mm	Width inner ring, upper tolerance
M A	64 Nm	Tightening torque
F Z	80.000 N	Cylinder Force
G r	CN	Radial Clearance
G rmin	0,03 mm	Radial clearance, minimum
G rmax	0,12 mm	Radial clearance, maximum

Mounting dimensions








r 1smin	0,6 mm	Edge Spacing
d 1	46 mm	Outer flange diameter inner ring



Temperature range

T_{\min}	-60 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment