


**GIHNRK40-LO**

## Rod end



Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN 24338 ISO 6982, open design

## Technical information

**Your current product variant**

|                           |                                      |                           |
|---------------------------|--------------------------------------|---------------------------|
| Clampable                 | Clampable                            |                           |
| Maintenance               | Maintenance required                 |                           |
| Mounting                  | Internal thread clampable            |                           |
| Lubrication nipple        | DIN71412-AM6 (tapered grease nipple) |                           |
| Slotted                   | Slotted, both sides                  |                           |
| Thread Pitch              | Right-hand thread                    |                           |
| Type of Sealing           | Without                              |                           |
| Radial internal clearance | CN (Group N)                         | Normal internal clearance |

**Main Dimensions & Performance Data**

|             |           |                                   |
|-------------|-----------|-----------------------------------|
| $C_r$       | 129.000 N | Basic dynamic load rating, radial |
| $C_{0r}$    | 219.000 N | Basic static load rating, radial  |
| $d$         | 40 mm     | Bore diameter bearing             |
| $d_2$       | 89 mm     | Outer eye diameter                |
| $l_4$       | 146 mm    | Total length internal thread head |
| $D$         | 62 mm     | Outside diameter bearing          |
| $B$         | 40 mm     | Width inner ring                  |
| $\approx m$ | 2,1 kg    | Weight                            |



## Dimensions

|          |          |  |
|----------|----------|--|
| $\alpha$ | 4 °      | Tilt angle                             |
| C 1      | 33 mm    | Width of the rod end                   |
| C 2      | 26 mm    | Width                                  |
| d K      | 53 mm    | Ball diameter                          |
| d 3      | M33x2    | Thread size                            |
| d 4      | 47 mm    | Shank diameter                         |
| d 5      | 80 mm    | Shank diameter, large                  |
| d 7      | M10x25   | Diameter screw clamp                   |
| h 1      | 97 mm    | Shank Length Internal thread head      |
| l 3      | 46 mm    | Thread length Internal thread          |
| l 7      | 41 mm    | Distance drilling with/shaft start     |
| d UT     | 0 mm     | Bore diameter bearing, lower tolerance |
| d T      | H7       | Bore diameter bearing, tolerance       |
| d OT     | 0,025 mm | Bore diameter bearing, upper tolerance |
| B UT     | -0,25 mm | Width inner ring, lower tolerance      |
| B OT     | 0 mm     | Width inner ring, upper tolerance      |
| M A      | 64 Nm    | Tightening torque                      |
| F Z      | 80.000 N | Cylinder Force                         |
| G r      | CN       | Radial Clearance                       |
| G rmin   | 0,03 mm  | Radial clearance, minimum              |
| G rmax   | 0,12 mm  | Radial clearance, maximum              |

## Mounting dimensions








|         |        |                                  |
|---------|--------|----------------------------------|
| r 1smin | 0,6 mm | Edge Spacing                     |
| d 1     | 46 mm  | Outer flange diameter inner ring |



### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -60 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment