



HXPC-50T [↗](#)

Mobile hydraulic heavy duty hook puller

BETEX HXPC, 2/3-arm self-centering, max. pull-off force 490 kN, with crane

Technical information

Your current product variant

| | | |
|--------|------|------------|
| Series | HXPC | With crane |
|--------|------|------------|

Technical data

| | | |
|---------------------|-------------------|---|
| U | 230 V | Voltage |
| | AC power | Current type |
| f | 50 – 60 Hz | Power frequency |
| s _{cm max} | 159 mm | Max. working stroke main cylinder |
| P _{max} | 700 bar | Max. operating pressure |
| w _{min} | 160 mm | Grip width, min. |
| w _{max} | 860 mm | Grip width, max. |
| t _{max} | 455 mm | Grip depth, max. |
| F _P | 490 kN | Pulling force |
| | 210 – 1550 | Working height range [bottom – center axis cylinder] (mm) |
| | 1850 x 970 x 1550 | Dimensions [LxWxH] (mm) |
| ≈m | 240 kg | Weight |



Additional information

electric 2-stage
hydraulic pump
operates cylinder
and crane, manual
operation of the self-
centering arms

Functional principle

two- or three-arm
puller (convertible)

Usability

mobile frame on
2 swivel castors and
2 fixed castors

Castors

Remote control,
2 adapter pieces
(total length
310 mm), security
blanket

Included in delivery