



View product details on medias

02.07.2026, 20:35:02 UTC

SCHAEFFLER



### **NSSF-1510** [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSSF Standard cylinder, single-acting, spring return, 15T class

#### Technical information

---



## Your current product variant

Series	NSSS	Standard cylinder
Version	15T	Capacity class 15

## Technical data

	15	Capacity class (tons)
$s_p$	254,5 mm	Stroke
$F_a$	166 kN	Advance force, max.
$P_{max}$	700 bar	Operating pressure, max.
$V_{oil}$	604 cm <sup>3</sup>	Oil capacity
A	373 mm	Height, retracted
B	627,5 mm	Height, extended
D	73 mm	Outer diameter
E	55 mm	Cylinder bore diameter
F	40 mm	Plunger diameter
H	25 mm	Base to advance port
J	38 mm	Saddle diameter
K	9,6 mm	Saddle protrusion from plunger
O	1"-8 UN	Plunger female thread (UN)
P	25,4 mm	Plunger thread length
U	47,7 mm	Base mounting holes, bolt circle
V	3/8"-16 UNC	Base mounting holes, thread (UNC)
Z	13 mm	Base mounting holes, thread depth
W	2 1/4"-16 UN	Collar thread (UN)
X	30 mm	Collar thread, length
≈m	9,5 kg	Weight



### Additional information

---

Hard chrome plated and  
hardened piston,  
Rolled inside of cylinder,  
Sandblasted outside  
with black nitride coating,  
Coupling with dust cap

Product specifics