



View product details on medias

25.06.2026, 17:52:29 UTC

SCHAEFFLER



### **NSSS-1514** [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSSS Standard cylinder, single-acting, spring return, 15T class

#### Technical information

---



## Your current product variant

Series	NSSS	Standard cylinder
Version	15T	Capacity class 15

## Technical data

	15	Capacity class (tons)
$s_p$	355,7 mm	Stroke
$F_a$	166 kN	Advance force, max.
$P_{max}$	700 bar	Operating pressure, max.
$V_{oil}$	845 cm <sup>3</sup>	Oil capacity
A	474,6 mm	Height, retracted
B	830,3 mm	Height, extended
D	73 mm	Outer diameter
E	55 mm	Cylinder bore diameter
F	40 mm	Plunger diameter
H	25 mm	Base to advance port
J	38 mm	Saddle diameter
K	9,6 mm	Saddle protrusion from plunger
O	1"-8 UN	Plunger female thread (UN)
P	25,4 mm	Plunger thread length
U	47,7 mm	Base mounting holes, bolt circle
V	3/8"-16 UNC	Base mounting holes, thread (UNC)
Z	13 mm	Base mounting holes, thread depth
W	2 1/4"-16 UN	Collar thread (UN)
X	30 mm	Collar thread, length
$\approx m$	11,8 kg	Weight



View product details on medias

25.06.2026, 17:52:29 UTC

SCHAEFFLER

### Additional information

---

Hard chrome plated and  
hardened piston,  
Rolled inside of cylinder,  
Sandblasted outside  
with black nitride coating,  
Coupling with dust cap

Product specifics