



View product details on medias

01.07.2026, 01:20:05 UTC

SCHAEFFLER



### **NSSF-55** [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSSF Standard cylinder, single-acting, spring return, 5T class

#### Technical information

---



### Your current product variant

Series	NSSS	Standard cylinder
Version	5T	Capacity class 5

### Technical data

	5	Capacity class (tons)
$s_p$	127 mm	Stroke
$F_a$	49,5 kN	Advance force, max.
$P_{max}$	700 bar	Operating pressure, max.
$V_{oil}$	90 cm <sup>3</sup>	Oil capacity
A	216 mm	Height, retracted
B	343 mm	Height, extended
D	38 mm	Outer diameter
E	30 mm	Cylinder bore diameter
F	25,4 mm	Plunger diameter
H	19 mm	Base to advance port
J	25 mm	Saddle diameter
K	6 mm	Saddle protrusion from plunger
O	3/4"-16 UN	Plunger female thread (UN)
P	14 mm	Plunger thread length
U	25 mm	Base mounting holes, bolt circle
V	1/4"-20 UNC	Base mounting holes, thread (UNC)
Z	14 mm	Base mounting holes, thread depth
W	1/2"-16 UN	Collar thread (UN)
X	28 mm	Collar thread, length
$\approx m$	1,9 kg	Weight



View product details on medias

01.07.2026, 01:20:05 UTC

SCHAEFFLER

### Additional information

---

Hard chrome plated and  
hardened piston,  
Rolled inside of cylinder,  
Sandblasted outside  
with black nitride coating,  
Coupling with dust cap

Product specifics