



View product details on medias

01.07.2026, 00:16:24 UTC

SCHAEFFLER



NSSF-59 [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSSF Standard cylinder, single-acting, spring return, 5T class

Technical information



Your current product variant

Series	NSSS	Standard cylinder
Version	5T	Capacity class 5

Technical data

	5	Capacity class (tons)
s_p	232 mm	Stroke
F_a	49,5 kN	Advance force, max.
P_{max}	700 bar	Operating pressure, max.
V_{oil}	164 cm ³	Oil capacity
A	324 mm	Height, retracted
B	556 mm	Height, extended
D	38 mm	Outer diameter
E	30 mm	Cylinder bore diameter
F	25,4 mm	Plunger diameter
H	19 mm	Base to advance port
J	25 mm	Saddle diameter
K	6 mm	Saddle protrusion from plunger
O	3/4"-16 UN	Plunger female thread (UN)
P	16 mm	Plunger thread length
U	25 mm	Base mounting holes, bolt circle
V	1/4"-20 UNC	Base mounting holes, thread (UNC)
Z	14 mm	Base mounting holes, thread depth
W	1 1/2"-16 UN	Collar thread (UN)
X	28 mm	Collar thread, length
≈m	2,8 kg	Weight



View product details on medias

01.07.2026, 00:16:24 UTC

SCHAEFFLER

Additional information

Hard chrome plated and
hardened piston,
Rolled inside of cylinder,
Sandblasted outside
with black nitride coating,
Coupling with dust cap

Product specifics