



View product details on medias

04.05.2026, 10:06:49 UTC

SCHAEFFLER



### **NSSS-256** [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSSS Standard cylinder, single-acting, spring return, 25T class

## Technical information

---



### Your current product variant

Series	NSSS	Standard cylinder
Version	25T	Capacity class 25

### Technical data

	25	Capacity class (tons)
$s_p$	158,5 mm	Stroke
$F_a$	269 kN	Advance force, max.
$P_{max}$	700 bar	Operating pressure, max.
$V_{oil}$	610 cm <sup>3</sup>	Oil capacity
A	273 mm	Height, retracted
B	431,5 mm	Height, extended
D	88 mm	Outer diameter
E	70 mm	Cylinder bore diameter
F	55 mm	Plunger diameter
H	25 mm	Base to advance port
J	50 mm	Saddle diameter
K	10,5 mm	Saddle protrusion from plunger
O	1½"-16 UN	Plunger female thread (UN)
P	25,4 mm	Plunger thread length
U	58 mm	Base mounting holes, bolt circle
V	1/2"-13 UNC	Base mounting holes, thread (UNC)
Z	19 mm	Base mounting holes, thread depth
W	3 5/16"-12 UN	Collar thread (UN)
X	50 mm	Collar thread, length
≈m	10 kg	Weight



View product details on medias

04.05.2026, 10:06:49 UTC

SCHAEFFLER

### Additional information

---

Hard chrome plated and  
hardened piston,  
Rolled inside of cylinder,  
Sandblasted outside  
with black nitride coating,  
Coupling with dust cap

Product specifics