

**FAG****684-2Z>N**

Deep groove ball bearing

Deep groove ball bearing 68...2Z, single row, shields, steel sheet metal cage

Technical information

**Your current product variant**

Version code	>N	Not marked on bearing
Type of Seal	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	4 mm	Bore diameter
D	9 mm	Outside diameter
B	4 mm	Width
C _r	680 N	Basic dynamic load rating, radial
C _{0r}	228 N	Basic static load rating, radial
C _{ur}	14,1 N	Fatigue load limit, radial
n _G	80.000 1/min	Limiting speed
n _{gr}	63.000 1/min	Reference speed
m	2 g	Weight



Mounting dimensions

$d_{a \min}$	4,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	8,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,1 mm	Maximum fillet radius

Dimensions

r_{\min}	0,1 mm	Minimum chamfer dimension
D_1	7,7 mm	Shoulder diameter outer ring
D_2	7,95 mm	Caliber diameter outer ring
d_1	5,3 mm	Shoulder diameter inner ring







Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	12,9	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides