


**GIR60-UK-2RS**

Rod end

Rod end with internal thread, maintenance-free, sliding layer: ELGOGLIDE, DIN ISO 12240-4, dimension series E, type F, inner ring curved surface with hard chromium coating, sealed, right hand thread

Technical information



Your current product variant

Clampable	Not clampable	
Maintenance	Maintenance free	
Mounting	Internal thread	
Lubrication nipple	Cannot be relubricated	
Slotted	No	
Thread Pitch	Right-hand thread	
Sealing	2RS	Lip seals on both sides

Main Dimensions & Performance Data

C_r	691.000 N	Basic dynamic load rating, radial
C_{0r}	405.000 N	Basic static load rating, radial
d	60 mm	Bore diameter bearing
d_2	135 mm	Outer eye diameter
l_4	242,5 mm	Total length internal thread head
$\approx m$	5,58 kg	Weight



Dimensions

C ₁	38 mm	Width of the rod end
D	90 mm	Outside diameter bearing
B	44 mm	Width inner ring
d _K	80 mm	Ball diameter
d ₃	M52x3	Thread size
d ₄	70 mm	Shank diameter
d ₅	88 mm	Shank diameter, large
h ₁	175 mm	Shank Length Internal thread head
α	6 °	Tilt angle
l ₃	70 mm	Thread length Internal thread
l ₅	20 mm	Length rod end shank
l ₇	75 mm	Distance drilling with/shaft start
W	75 mm	Width Across Flat
d _{UT}	-0,015 mm	Bore diameter bearing, lower tolerance
d _T	0,015	Bore diameter bearing, tolerance
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,15 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
G _r	0 - 0,06	Radial Clearance
G _{rmin}	0 mm	Radial clearance, minimum
G _{rmax}	0,06 mm	Radial clearance, maximum

Mounting dimensions








r _{1smin}	1 mm	Edge Spacing
d ₁	66,8 mm	Outer flange diameter inner ring



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	130 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Sealed on both sides
-  Static angular error and misalignment
-  Dynamic angular error and misalignment