

**GAL70-UK-2RS**

## Rod end

Rod end with external thread, left hand thread, maintenance-free, sliding layer: ELGOGLIDE, DIN ISO 12240-4, dimension series E, type M, inner ring curved surface with hard chromium coating, sealed

## Technical information

**Your current product variant**

Clampable	Not clampable	
Grease nipples	Cannot be relubricated	
Slotted	No	
Thread Pitch	Left-hand thread	
Maintenance	Maintenance free	
Sealing	2RS	Lip seals on both sides
Material sliding Layer	ELGOGLIDE	
Mounting	External thread	

**Main Dimensions & Performance Data**

d <sub>2</sub>	160 mm	Outer diameter eye
C <sub>r</sub>	883.000 N	Basic dynamic load rating
C <sub>0r</sub>	547.000 N	Basic static load rating
d	70 mm	Bore diameter bearing
D	105 mm	Outside diameter bearing
l <sub>2</sub>	315 mm	Total length
B	49 mm	Width inner ring
≈m	8,72 kg	Weight



## Dimensions

$d_k$	92 mm	Ball diameter
$d_1$	77,9 mm	Outer flange diameter inner ring
$d_3$	M56x4	Thread size
$h$	235 mm	Length of thread
$C_1$	42 mm	Width of the rod end
$\alpha$	6 °	Tilt angle
$l_1$	125 mm	Thread length
$l_7$	87 mm	Length of the flat surface from the bearing bore centre to the shank
$B_{UT}$	-0,15 mm	Width inner ring , lower tolerance
$B_{OT}$	0 mm	Width inner ring; upper tolerance
$d_T$	0,015	Bore diameter_bearing_tolerance
$d_{UT}$	-0,015 mm	Bore diameter, lower tolerance
$d_{OT}$	0 mm	Bore diameter bearing upper tolerance
$G_r$	0 - 0,072 mm	Radial clearance
$G_{rmax}$	0,072 mm	Radial clearance, maximum
$G_{rmin}$	0 mm	Radial clearance, minimum

## Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	130 °C	Operating temperature max.








## Mounting dimensions

$r_{1s}$	1 mm	Smallest single chamfer dimension, inner ring
----------	------	---



## Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Sealed on both sides
-  Static angular error and misalignment
-  Dynamic angular error and misalignment