



## KWEM12-E-WL-V1-G2 [↗](#)

Miniature Carriage, Standard for Miniature-Guideway, Standard

Miniature-Carriage, Wide-Long design; for Miniature guideway, Wide design


### Technical information

#### Your current product variant

Size Code	12	
Version	E	
Carriage design	WL	Wide, long design
Preload	V1	Preload class 1
Accuracy class	G2	

#### Main Dimensions & Performance Data

H	14 mm	Height system
B	40 mm	Width carriage
L	58 mm	Length of carriage
C	4.250 N	Dynamic load rating
C <sub>0</sub>	8.300 N	Basic static load capacity
M <sub>0x</sub>	96,8 Nm	Static moment rating about X axis
M <sub>0y</sub>	57,9 Nm	Static moment rating about Y axis
M <sub>0z</sub>	57,9 Nm	Static moment rating about Z axis
≈m	118 g	Weight





### Mounting dimensions

b	24 mm	Width rail
A <sub>1</sub>	8 mm	Distance from locating edge on carriage to locating edge on guideway
A <sub>2</sub>	6 mm	Distance from locating edge to hole
H <sub>1</sub>	3 mm	Free space, system dimension
J <sub>B</sub>	28 mm	Hole spacing
J <sub>L</sub>	28 mm	Hole Spacing
T <sub>5</sub>	3,5 mm	Thread depth
A <sub>3</sub>	2,7 mm	Position lubrication connector
G2	M3	Thread size
G2 M <sub>A</sub>	1,1 Nm	Maximum tightening torque

### Additional information

VMKB_065	KWEM	Material name
----------	------	---------------