

**FAG****6322-M-J20GA-C4**

Deep groove ball bearing

Deep groove ball bearing 63..-M-J20GA,  
single row, solid brass cage, ceramic coated

## Technical information



## Your current product variant

|                                  |              |   |
|----------------------------------|--------------|---|
| Sealing                          | Without      | Not sealed                                    |
| Cage                             | M            | Solid brass cage, rolling element guided      |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                         |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150°       |
| Lubricant                        | Without      | Bearing not greased                           |
| Radial internal clearance        | C4 (Group 4) | Internal clearance larger than C3             |
| Bore type                        | Z            | Cylindrical                                   |
| Coating                          | J20GA        | Current insulation, outer ring ceramic coated |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 110 mm      | Bore diameter                     |
| D               | 240 mm      | Outside diameter                  |
| B               | 50 mm       | Width                             |
| C <sub>r</sub>  | 201.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 165.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 8.800 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.950 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.150 1/min | Reference speed                   |
| ≈m              | 11,5 kg     | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 124 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 226 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,5 mm | Maximum fillet radius                |

### Dimensions

|            |           |                              |
|------------|-----------|------------------------------|
| $r_{\min}$ | 3 mm      | Minimum chamfer dimension    |
| $D_1$      | 198,1 mm  | Shoulder diameter outer ring |
| $d_1$      | 153,26 mm | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,8 | Calculation factor |
|-------|------|--------------------|

### Characteristics

|   |                              |
|---|------------------------------|
|  | Radial load                  |
|  | Axial load in one direction  |
|  | Axial load in two directions |
|  | Grease Lubrication           |
|  | Oil Lubrication              |
|  | Not sealed                   |
|  | Current insulated            |