

**FAG****6207-C-C4>V**

Deep groove ball bearing

Deep groove ball bearing 62...-C, single row,  
Generation C, steel sheet metal cage

## Technical information

**Your current product variant**

|                                  |              |   |
|----------------------------------|--------------|---|
| Version code                     | >V           | Not marked on bearing                   |
| Changed internal design          | C            | GenerationC                             |
| Sealing                          | Without      | Not sealed                              |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | P6           | Class6 (P6), better then PN             |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | C4 (Group 4) | Internal clearance larger than C3       |
| Bore type                        | Z            | Cylindrical                             |

**Main Dimensions & Performance Data**

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 35 mm        | Bore diameter                     |
| D               | 72 mm        | Outside diameter                  |
| B               | 17 mm        | Width                             |
| C <sub>r</sub>  | 29.500 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 15.400 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.060 N      | Fatigue load limit, radial        |
| n <sub>G</sub>  | 15.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 11.300 1/min | Reference speed                   |
| ≈m              | 0,265 kg     | Weight                            |



### Mounting dimensions

|              |       |                                      |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 42 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 65 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1 mm  | Maximum fillet radius                |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1,1 mm   | Minimum chamfer dimension    |
| $D_1$      | 61,56 mm | Shoulder diameter outer ring |
| $D_2$      | 64,51 mm | Caliber diameter outer ring  |
| $d_1$      | 46,89 mm | Shoulder diameter inner ring |
| $d_2$      | 44,61 mm | Caliber diameter inner ring  |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,9 | Calculation factor |
|-------|------|--------------------|

### Characteristics

|   |                              |
|---|------------------------------|
|  | Radial load                  |
|  | Axial load in one direction  |
|  | Axial load in two directions |
|  | Grease Lubrication           |
|  | Oil Lubrication              |
|  | Not sealed                   |