

**FAG****61819-2RZ-C3**

Deep groove ball bearing

Deep groove ball bearing 618..-2RZ, single row, shields, steel sheet metal cage

Technical information



Your current product variant

Type of Seal	2RZ	Non-contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	120 mm	Outside diameter
B	13 mm	Width
C _r	21.000 N	Basic dynamic load rating, radial
C _{0r}	21.300 N	Basic static load rating, radial
C _{ur}	1.230 N	Fatigue load limit, radial
n _G	6.600 1/min	Limiting speed
n _{gr}	4.350 1/min	Reference speed
m	0,302 kg	Weight



Mounting dimensions

$d_{a \min}$	99,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	115,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
D_1	112,07 mm	Shoulder diameter outer ring
D_2	114,2 mm	Caliber diameter outer ring
d_1	103,2 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Calculation factors

f_0	16,1	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides