

**FAG****61820-C4**

Deep groove ball bearing

Deep groove ball bearing 618, single row,  
steel sheet metal cage

## Technical information

**Your current product variant**

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	100 mm	Bore diameter
D	125 mm	Outside diameter
B	13 mm	Width
$C_r$	21.300 N	Basic dynamic load rating, radial
$C_{0r}$	22.100 N	Basic static load rating, radial
$C_{ur}$	1.250 N	Fatigue load limit, radial
$n_G$	7.400 1/min	Limiting speed
$n_{gr}$	4.150 1/min	Reference speed
$m$	0,315 kg	Weight



### Mounting dimensions

$d_{a \min}$	104,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	120,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	117,07 mm	Shoulder diameter outer ring
$d_1$	108,2 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	16	Calculation factor
-------	----	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed