


**KWLT20-A-V0-G3**

Recirculating ball bearing carriage

Standard flanged carriage, standard end plate,
for four-row linear recirculating ball bearing
and guideway assembly



Technical information

**Your current product variant**

| | | |
|-----------------|----|------------------|
| Size code | 20 | |
| Carriage design | A | Standard design |
| Preload | V0 | Slight clearance |
| Accuracy class | G3 | |

Main Dimensions & Performance Data

| | | |
|-----------------|----------|------------------------------------|
| H | 30 mm | Height system |
| B | 63 mm | Width carriage |
| L | 71,8 mm | Overall length carriage |
| C | 12.300 N | Dynamic load rating |
| C ₀ | 22.400 N | Basic static load capacity |
| M _{0x} | 244 Nm | Static moment rating about X-axis |
| M _{0y} | 173 Nm | Static moment rating about Y-axis |
| M _{0z} | 173 Nm | Static moment rating about Z-axis |
| M _{0x} | 122 Nm | Dynamic moment rating about X-axis |
| M _{0y} | 154 Nm | Dynamic moment rating about y-axis |
| M _{0z} | 154 Nm | Dynamic moment rating about Z-axis |
| ≈m | 400 g | Weight |



Mounting dimensions

| | | |
|-------------------|---------|--|
| A ₁ | 21,5 mm | Distance from locating edge on carriage to locating edge on guideway |
| A ₂ | 5 mm | Distance from locating edge to hole |
| L ₁ | 50 mm | Carrier length |
| H ₁ | 5 mm | Free space, system dimension |
| J _B | 53 mm | Hole spacing |
| J _L | 40 mm | Hole Spacing |
| A ₃ | 5,7 mm | Position lubrication connector |
| T ₅ | 9 mm | Thread depth |
| G ₂ | M6 | Thread size, DIN ISO 4762-12.9 |
| G2 M _A | 16,5 Nm | Maximum tightening torque |

Additional information

| | | |
|----------|------|---------------|
| VMKB_065 | KWLT | Material name |
|----------|------|---------------|