

**KWLT25-AL-V1-G4** [↗](#)

## Recirculating ball bearing carriage

Long flanged carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

## Technical information

**Your current product variant**

Size code	25	
Carriage design	AL	Long design
Preload class	V1	Slight preload (standard)
Accuracy class	G4	

**Main Dimensions & Performance Data**

H	36 mm	Height system
B	70 mm	Width carriage
L	103,9 mm	Overall length carriage
C	24.300 N	Dynamic load rating
C <sub>0</sub>	48.500 N	Basic static load capacity
M <sub>0x</sub>	640 Nm	Static moment rating about X-axis
M <sub>0y</sub>	590 Nm	Static moment rating about Y-axis
M <sub>0z</sub>	590 Nm	Static moment rating about Z-axis
M <sub>0x</sub>	287 Nm	Dynamic moment rating about X-axis
M <sub>0y</sub>	490 Nm	Dynamic moment rating about y-axis
M <sub>0z</sub>	490 Nm	Dynamic moment rating about Z-axis
m	0,81 kg	Weight



### Mounting dimensions

---

A <sub>1</sub>	23,5 mm	Distance from locating edge on carriage to locating edge on guideway
A <sub>2</sub>	6,5 mm	Distance from locating edge to hole
L <sub>1</sub>	79,1 mm	Carrier length
H <sub>1</sub>	7 mm	Free space, system dimension
J <sub>B</sub>	57 mm	Hole spacing
J <sub>L</sub>	45 mm	Hole Spacing
A <sub>3</sub>	6,5 mm	Position lubrication connector
T <sub>5</sub>	12 mm	Thread depth
G <sub>2</sub>	M8	Thread size, DIN ISO 4762-12.9
G2 M <sub>A</sub>	40 Nm	Maximum tightening torque

### Additional information

---

VMKB_065	KWLT	Material name
----------	------	---------------