


**KWLT35-HL-V2-G4** [↗](#)

## Recirculating ball bearing carriage

Long & high carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

## Technical information

**Your current product variant**

|                 |    |                   |
|-----------------|----|-------------------|
| Size code       | 35 |                   |
| Carriage design | HL | High, long design |
| Preload         | V2 | Preload class 2   |
| Accuracy class  | G4 |                   |

**Main Dimensions & Performance Data**

|                 |          |                                    |
|-----------------|----------|------------------------------------|
| H               | 55 mm    | Height system                      |
| B               | 70 mm    | Width carriage                     |
| L               | 142,5 mm | Overall length carriage            |
| C               | 45.000 N | Dynamic load rating                |
| C <sub>0</sub>  | 86.000 N | Basic static load capacity         |
| M <sub>0x</sub> | 1.680 Nm | Static moment rating about X-axis  |
| M <sub>0y</sub> | 1.390 Nm | Static moment rating about Y-axis  |
| M <sub>0z</sub> | 1.390 Nm | Static moment rating about Z-axis  |
| M <sub>0x</sub> | 807 Nm   | Dynamic moment rating about X-axis |
| M <sub>0y</sub> | 1.224 Nm | Dynamic moment rating about y-axis |
| M <sub>0z</sub> | 1.224 Nm | Dynamic moment rating about Z-axis |
| ≈m              | 1,92 kg  | Weight                             |



### Mounting dimensions

|                   |          |  |
|-------------------|----------|--|
| A <sub>1</sub>    | 18 mm    | Distance from locating edge on carriage to locating edge on guideway |
| A <sub>2</sub>    | 10 mm    | Distance from locating edge to hole                                  |
| L <sub>1</sub>    | 105,5 mm | Carrier length   |
| H <sub>1</sub>    | 9,5 mm   | Free space, system dimension   |
| J <sub>B</sub>    | 50 mm    | Hole spacing   |
| J <sub>L</sub>    | 72 mm    | Hole Spacing   |
| A <sub>3</sub>    | 15 mm    | Position lubrication connector                                       |
| T <sub>5</sub>    | 17 mm    | Thread depth   |
| G <sub>2</sub>    | M8       | Thread size, DIN ISO 4762-12.9                                       |
| G2 M <sub>A</sub> | 40 Nm    | Maximum tightening torque  |

### Additional information

|          |      |               |
|----------|------|---------------|
| VMKB_065 | KWLT | Material name |
|----------|------|---------------|